

CSS14-34-S-SD-M-ST

- Actuation from side
- Thermoplastic enclosure
- 27 mm x 108.2 mm x 35 mm
- serial diagnostic output
- Misaligned actuation possible
- 1 x connector plug M12, 8-pole
- Electronic contact-free, coded system
- Max. length of the sensor chain 200 m
- Max. 31 sensors can be wired in series.
- 2 short-circuit proof PNP safety outputs
- High repeat accuracy of the switching points
- Integral cross-short, wire-breakage and external voltage monitoring of the safety cables up to the control cabinet



Data

General data

Product name	CSS 34
Standards	IEC 60947-5-3
Active principle	inductive
Housing construction form	Block
Installation conditions (mechanical)	not flush
Sensor topology	Sensor for series wiring
Enclosure material	Glass-fibre, reinforced thermoplastic
Active area	Glass-fibre, reinforced thermoplastic
Gross weight	140 g
Reaction time, maximum	30 ms
Duration of risk, maximum	60 ms

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 27.11.2020 02:25:15