

## MZM100BST-AS-REMAP



- Power to lock
- Permanent magnet
- Solenoid interlock
- Automatic latching
- Actuator monitored
- Intelligent diagnosis
- 40 mm x 179 mm x 40 mm
- Thermoplastic enclosure
- Integrated AS-Interface
- 3 LEDs to show operating conditions
- Electronic contact-free, coded system
- Solenoid interlocks (for the protection of man) with innovating and unique operating principle
- Sensor technology permits an offset between actuator and interlock of  $\pm 5$  mm vertically and  $\pm 3$  mm horizontally

### Data

#### General data

Product name	MZM 100 AS
	IEC 60947-5-3
	ISO 13849-1
Standards	EN 60947-5-1
	EN 62026-2
	IEC 61508
general information	Universal coding
Coding level according to ISO 14119	Low
Active principle	inductive
Enclosure material	Glass-fibre, reinforced thermoplastic
Gross weight	631 g
Time to readiness, maximum	4,000 ms
Reaction time, maximum	150 ms
Duration of risk, maximum	150 ms

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 19.11.2020 05:29:29