

BDF200-ST1-AS-NHK-SWS20-LTWH-LTBU-G24



- Thermoplastic enclosure
- Suitable for AS-i Power24
- slender shock-proof enclosure
- with connector plug M12 bottom
- Illuminated pushbutton blue for reset/start
- to be installed at an ergonomic favourable position
- Illuminated pushbutton white e.g. for automatic stop
- Indicator lamp G24 for “emergency stop actuated”
- Key selector switch e.g. for authorisation to operate
- Emergency stop latching pushbutton with protective collar
- to be fitted to commercial-off-the-shelf aluminium profiles
- Two-layer plastic identification labels can be used (engravements on request)
- Integrated AS-Interface, Safety Slave for emergency stop and A/B Slave for command and signalling devices

Data

General data

Product name BDF200AS (Preferred types)

	IEC 61508
	ISO 13849-1
Standards	EN 60947-5-1
	EN ISO 13850
	EN 62026-2
Climatic stress	DIN EN 60068
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Gross weight	280 g
Reaction time, maximum	100 ms
Positions used, position 1	Emergency stop, with protective collar
Positions used, position 2	Key switch, 2 switching positions
Positions used, position 3	Illuminated pushbutton, white
Positions used, position 4	Illuminated pushbutton, blue

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 19.11.2020 11:03:54