

BDF200-ST1-AS-NHK-LMRD-LTWH-LTBU



- **Thermoplastic enclosure**
- **Suitable for AS-i Power24**
- **slender shock-proof enclosure**
- **with connector plug M12 bottom**
- **Illuminated pushbutton blue for reset/start**
- **Illuminated pushbutton white for automatic stop**
- **to be installed at an ergonomic favourable position**
- **Signalling device red for “emergency stop actuated”**
- **Emergency stop latching pushbutton with protective collar**
- **to be fitted to commercial-off-the-shelf aluminium profiles**
- **Two-layer plastic identification labels can be used (engravements on request)**
- **Integrated AS-Interface, Safety Slave for emergency stop and A/B Slave for command and signalling devices**

Data

General data

Product name	BDF200AS (Preferred types)
	IEC 61508
Standards	ISO 13849-1
	EN 60947-5-1
	EN ISO 13850
	EN 62026-2
Climatic stress	DIN EN 60068
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing

Gross weight	280 g
Reaction time, maximum	100 ms
Positions used, position 1	Emergency stop, with protective collar
Positions used, position 2	Illuminated signal, red
Positions used, position 3	Illuminated pushbutton, white
Positions used, position 4	Illuminated pushbutton, blue

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on