

RSS36-I2-D-ST



- Actuation from side
- Thermoplastic enclosure
- 27 mm x 108.2 mm x 35 mm
- Misaligned actuation possible
- 1 x connector socket M12, 8-pole
- 2 short-circuit proof PNP safety outputs
- Coding level "High" according to ISO 14119
- High repeat accuracy of the switching points
- Repeated individual coding with RFID technology
- RFID-technology for needs-based protection against tampering
- Integral cross-short, wire-breakage and external voltage monitoring of the safety cables up to the control cabinet

Data

General data

Product name	RSS 36
Standards	IEC 60947-5-3
general information	Individual coding, multiple teaching
Coding level according to ISO 14119	High
Active principle	RFID
Housing construction form	Block
Installation conditions (mechanical)	not flush
Sensor topology	Sensor for series wiring
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Active area	Glass-fibre, reinforced thermoplastic
Gross weight	80 g
Time to readiness, maximum	2,000 ms
Reaction time, maximum	100 ms
Duration of risk, maximum	200 ms

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 20.11.2020 03:51:59