

## AZM400Z-ST2-I1-2P2P-T-E

- Emergency exit
- 2 Diagnostic outputs
- Clamping force 10.000
- Guard locking monitored
- Bistable, motor-driven system
- 2 Connector M12, 8- and 5-poles
- High tolerance to door misalignment
- Individual coding with RFID technology
- Coding level "High" according to ISO 14119
- Operation on P/P- and P/N-switching outputs
- Electric manual release with auxiliary voltage
- Release possible against lateral forces up to 300 N
- Two-channel input signal of the guard locking function
- PL e / cat. 4 / SIL 3 for interlocking and guard locking function



## Data

### General data

Product name	AZM 400
Standards	IEC 60947-5-1
	ISO 13849-1
	IEC 61508
general information	ISO 14119
	Individual coding
Coding level according to ISO 14119	High
Active principle	Magnetic field
Enclosure material	RFID
	Light alloy die-casting
Gross weight	774 g
Time to readiness, maximum	1,500 ms
Reaction time, maximum	100 ms

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 20.11.2020 07:52:56