

RSS16-I2-D-R-ST8H



- with latching
- Series-wiring unlimited
- Thermoplastic enclosure
- Suitable for series-wiring
- 1 x connector plug M12, 8-pole
- Door stop with magnetic latching
- 3 different directions of actuation
- Connection terminal or plug connection
- Coding level "High" according to ISO 14119
- Repeated individual coding with RFID technology
- RFID-technology for needs-based protection against tampering

Data

General data

Product name	RSS16
Standards	IEC 60947-5-3
general information	Individual coding, multiple teaching
Coding level according to ISO 14119	High
Active principle	RFID
Housing construction form	Block
Installation conditions (mechanical)	not flush
Sensor topology	Sensor for series wiring
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Active area	Glass-fibre, reinforced thermoplastic
Gross weight	275 g
Time to readiness, maximum	2,000 ms
Reaction time, maximum	100 ms
Duration of risk, maximum	200 ms

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 20.11.2020 10:26:17