

AZM300Z-I1-ST-AS-P



- Power to unlock
- Guard locking monitored
- Thermoplastic enclosure
- High protection class IP69K
- 2 integrated snap-in stages
- Solenoid supply 24 VDC (Aux)
- 3 different directions of actuation
- Suitable for hinged and sliding guards
- Individual coding with RFID technology
- Coding level "High" according to ISO 14119
- I-variants with coding level HIGH to ISO 14119
- Solenoid interlock with integrated AS-i Safety Interface
- Universal repeatedly teachable or individual coding because of the RFID technology

Data

General data

Product name	AZM 300-AS
	IEC 61508
	ISO 13849-1
Standards	EN 60947-5-1
	ISO 14119
	EN 62026-2
general information	Individual coding
Coding level according to ISO 14119	High
Active principle	RFID
Enclosure material	Glass-fibre, reinforced thermoplastic
Gross weight	618.2 g
Time to readiness, maximum	5,000 ms
Reaction time, maximum	120 ms
Duration of risk, maximum	200 ms

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 23.11.2020 03:31:11