

AZM300Z-I2-ST-SD2P-T



- Series-wiring
- Compact design
- Manual release
- Emergency exit
- Power to unlock
- Connector M12, 8-pole
- Thermoplastic enclosure
- Guard locking monitored
- serial diagnostic output
- 3 different directions of actuation
- 3 LEDs to show operating conditions
- Suitable for hinged and sliding guards
- Suitable for mounting to profile systems
- Coding level "High" according to ISO 14119
- Repeated individual coding with RFID technology
- RFID-technology for needs-based protection against tampering

Data

General data

Product name	AZM 300
	ISO 13849-1
	IEC 61508
Standards	IEC 60947-5-3
	ISO 14119
	IEC 62061
general information	Individual coding, multiple teaching
Coding level according to ISO 14119	High
Active principle	RFID
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Gross weight	660.1 g
Time to readiness, maximum	5,000 ms
Duration of risk, maximum	200 ms

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 23.11.2020 08:27:00