

AZM201Z-I2-ST2-T-1P2PW-A



- Power to lock
- Manual release
- Intelligent diagnosis
- Thermoplastic enclosure
- Guard locking monitored
- Self-monitoring series-wiring
- 3 LEDs to show operating conditions
- Max. length of the sensor chain 200 m
- Suitable for hinged and sliding guards
- Coding level "High" according to ISO 14119
- Repeated individual coding with RFID technology
- RFID-technology for needs-based protection against tampering
- Sensor technology permits an offset between actuator and interlock of ± 5 mm vertically and ± 3 mm horizontally

Data

General data

Product name	AZM 201
Standards	IEC 60947-5-1
	ISO 13849-1
	IEC 61508
	IEC 60947-5-3
	ISO 14119
	IEC 62061
general information	Individual coding, multiple teaching
Coding level according to ISO 14119	High
Active principle	RFID
Enclosure material	Glass-fibre, reinforced thermoplastic
Gross weight	593.1 g
Time to readiness, maximum	4,000 ms
Duration of risk, maximum	200 ms

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 24.11.2020 04:44:35