

## BDF200-SD-NH-LT-LT-LT-2875



- Connector M12, 8-pole
- Thermoplastic enclosure
- E-STOP with electronic OSSDs
- slender shock-proof enclosure
- Device version for integration in SD-Interface systems
- Integrated SD interface for command and signaling devices
- to be fitted to commercial-off-the-shelf aluminium profiles

### Data

#### General data

|                            |   |
|----------------------------|---|
| Product name               | BDF 200-SD  |
|                            | IEC 60947-5-1   |
|                            | ISO 13849-1   |
| Standards                  | IEC 61508   |
|                            | IEC 60947-5-5   |
|                            | ISO 13850   |
| Climatic stress            | IEC 60947-5-5   |
| Terminal (mechanical)      | Connector plug M12, 8-pole, A-coded                               |
| Enclosure material         | Plastic, glass-fibre reinforced thermoplastic, self-extinguishing |
| Gross weight               | 280 g   |
| Reaction time, maximum     | 50 ms   |
| Duration of risk, maximum  | 100 ms  |
| Positions used, position 1 | NH, Emergency stop  |
| Positions used, position 2 | LT-2875, Illuminated pushbutton                                   |
| Positions used, position 3 | LT-2875, Illuminated pushbutton                                   |
| Positions used, position 4 | LT-2875, Illuminated pushbutton                                   |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 24.11.2020 08:54:31