

BDF200-FB-NH-LT-LT-LT-2875



- Connector M12, 8-pole
- Thermoplastic enclosure
- E-STOP with electronic OSSDs
- slender shock-proof enclosure
- Device version for connection to a Safety-Field-Box SFB
- Integrated FB interface for command and signaling devices
- to be fitted to commercial-off-the-shelf aluminium profiles

Data

General data

Product name	BDF 200-FB
	IEC 60947-5-1
	ISO 13849-1
Standards	IEC 61508
	IEC 60947-5-5
	ISO 13850
Climatic stress	IEC 60947-5-5
Terminal (mechanical)	Connector plug M12, 8-pole, A-coded
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Gross weight	280 g
Reaction time, maximum	50 ms
Duration of risk, maximum	100 ms
Positions used, position 1	NH, Emergency stop
Positions used, position 2	LT-2875, Illuminated pushbutton
Positions used, position 3	LT-2875, Illuminated pushbutton
Positions used, position 4	LT-2875, Illuminated pushbutton

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 24.11.2020 08:56:55