

## AZ201-I2-CC-T-1P2P



- Intelligent diagnosis
- Thermoplastic enclosure
- 3 LEDs to show operating conditions
- Max. length of the sensor chain 200 m
- Suitable for hinged and sliding guards
- Coding level "High" according to ISO 14119
- Self-monitoring series-wiring of 31 sensors
- Repeated individual coding with RFID technology
- RFID-technology for needs-based protection against tampering
- Sensor technology permits an offset between actuator and interlock of  $\pm 5$  mm vertically and  $\pm 3$  mm horizontally

### Data

#### General data

Product name	AZ 201
	IEC 60947-5-1
	ISO 13849-1
Standards	IEC 61508
	IEC 60947-5-3
	ISO 14119
	IEC 62061
general information	Individual coding, multiple teaching
Coding level according to ISO 14119	High
Active principle	RFID, 125 kHz
Enclosure material	Glass-fibre, reinforced thermoplastic
Gross weight	392.3 g
Time to readiness, maximum	4,000 ms
Duration of risk, maximum	200 ms

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 24.11.2020 09:29:43