

## AZM201Z-ST-T-1P2PW-2965-1



- Manual release
- Intelligent diagnosis
- Thermoplastic enclosure
- Self-monitoring series-wiring
- 3 LEDs to show operating conditions
- Max. length of the sensor chain 200 m
- Suitable for hinged and sliding guards
- RFID-technology for needs-based protection against tampering
- Sensor technology permits an offset between actuator and interlock of  $\pm 5$  mm vertically and  $\pm 3$  mm horizontally

### Data

#### General data

|                                     |                                       |
|-------------------------------------|---------------------------------------|
| Product name                        | AZM 201                               |
|                                     | IEC 60947-5-1                         |
|                                     | ISO 13849-1                           |
| Standards                           | IEC 61508                             |
|                                     | IEC 60947-5-3                         |
|                                     | ISO 14119                             |
|                                     | IEC 62061                             |
| general information                 | Universal coding                      |
| Coding level according to ISO 14119 | Low                                   |
| Active principle                    | RFID                                  |
| Enclosure material                  | Glass-fibre, reinforced thermoplastic |
| Gross weight                        | 610 g                                 |
| Time to readiness, maximum          | 4,000 ms                              |
| Duration of risk, maximum           | 200 ms                                |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 25.11.2020 03:45:53