

AZM201Z-I2-ST-T-AS-A-P



- Long life
- Double-insulated
- 40 mm x 244 mm x 50 mm
- Thermoplastic enclosure
- High holding force 2000
- Integrated AS-Interface
- I-variants with coding level HIGH to ISO 14119
- Interlock with protection against incorrect locking.
- Solenoid interlock with integrated AS-i Safety Interface
- Universal repeatedly teachable or individual coding because of the RFID technology

Data

General data

| | |
|-------------------------------------|---------------------------------------|
| Product name | Z 256 roller lever 7H-2138 |
| | ISO 13849-1 |
| | IEC 61508 |
| Standards | IEC 60947-5-3 |
| | ISO 14119 |
| | IEC 62061 |
| | EN 62026-2 |
| general information | Individual coding, multiple teaching |
| Coding level according to ISO 14119 | High |
| Active principle | RFID |
| Enclosure material | Glass-fibre, reinforced thermoplastic |
| Gross weight | 538.5 g |
| Time to readiness, maximum | 4,000 ms |
| Reaction time, maximum | 100 ms |
| Duration of risk, maximum | 200 ms |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 25.11.2020 03:55:34