

Product availability : Stock - Normally stocked in distribution facility

Price* : 3597.20 USD



Main

Range of product	Modicon Quantum automation platform
Product or component type	DIO head-end adaptor

Complementary

Product compatibility	140CRA21110 140CRA21120
Number of port	1 Modbus Plus RS485 twisted pair single copper 1 Modbus RS232 twisted pair single copper
Transmission rate	1 Mbit/s
I/O words	30 I/32 O
Checks	Checksum Processor RAM address RAM
Power dissipation in W	4 W
Bus current requirement	780 mA
Module format	Standard

Environment

Resistance to electrostatic discharge	4 kV contact conforming to IEC 801-2 8 kV on air conforming to IEC 801-2
Resistance to electromagnetic fields	9.14 V/yd (10 V/m) 80...2000 MHz conforming to IEC 801-3
Ambient air temperature for operation	32...140 °F (0...60 °C)
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Relative humidity	95 % without condensation
Operating altitude	<= 16404.2 ft (5000 m)
Protective treatment	Conformal coating Humiseal 1A33

Standards	UL 508
Product certifications	FM Class 1 Division 2 CSA C-Tick RMRS GOST

Ordering and shipping details


Category	18150 - QUANTUM CONTROLLERS,HSBY,COMM.
Discount Schedule	PC21
GTIN	00785901556145
Nbr. of units in pkg.	1
Package weight(Lbs)	2.21
Returnability	N
Country of origin	FR

Contractual warranty

Warranty period	18 months
-----------------	-----------

Racks for Modules Mounting

Dimensions of Modules and Racks



- (1) 2 slots
- (2) 3 slots
- (3) 4 slots
- (4) 6 slots
- (5) 10 slots
- (6) 16 slots