

SIMATIC PM1507/1AC/24VDC/3A
 SIMATIC PM 1507 24 V/3 A Stabilized power supply for SIMATIC
 S7-1500 input: 120/230 V AC, output: 24 V DC/3 A



Input	
Input	1-phase AC
<ul style="list-style-type: none"> Note 	Automatic range selection
supply voltage	
<ul style="list-style-type: none"> 1 at AC rated value 2 at AC rated value 	120 V 230 V
input voltage	
<ul style="list-style-type: none"> 1 at AC 2 at AC 	85 ... 132 V 170 ... 264 V
Wide-range input	No
Overvoltage resistance	2.3 × Vin rated, 1.3 ms
Mains buffering	at Vin = 93/187 V
Mains buffering at lout rated, min.	20 ms; at Vin = 93/187 V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	45 ... 65 Hz
input current	
<ul style="list-style-type: none"> at rated input voltage 120 V at rated input voltage 230 V 	1.4 A 0.8 A

Switch-on current limiting (+25 °C), max.	23 A
duration of inrush current limiting at 25 °C	
• maximum	3 ms
I ² t, max.	1.3 A ² ·s
Built-in incoming fuse	T 3,15 A/250 V (not accessible)
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: 10 A characteristic B or 6 A characteristic C

Output

Output	Controlled, isolated DC voltage
Rated voltage V _{out} DC	24 V
Total tolerance, static ±	1 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	0.1 %
Residual ripple peak-peak, max.	50 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	150 mV
product function output voltage adjustable	No
Status display	LED green for 24 V OK; LED red for error; LED yellow for stand-by
On/off behavior	No overshoot of V _{out} (soft start)
Startup delay, max.	1.5 s
Voltage rise, typ.	10 ms
Rated current value I _{out} rated	3 A
Current range	0 ... 3 A
supplied active power typical	72 W
short-term overload current	
• on short-circuiting during the start-up typical	12 A
• at short-circuit during operation typical	12 A
duration of overloading capability for excess current	
• on short-circuiting during the start-up	70 ms
• at short-circuit during operation	70 ms
Parallel switching for enhanced performance	No

Efficiency

Efficiency at V _{out} rated, I _{out} rated, approx.	87 %
Power loss at V _{out} rated, I _{out} rated, approx.	11 W

Closed-loop control

Dynamic mains compensation (V _{in} rated ±15 %), max.	0.1 %
Dynamic load smoothing (I _{out} : 50/100/50 %), U _{out} ± typ.	1 %
Dynamic load smoothing (I _{out} : 10/90/10 %), U _{out} ± typ.	3 %
Load step setting time 10 to 90%, typ.	5 ms
Load step setting time 90 to 10%, typ.	5 ms

setting time maximum	5 ms
----------------------	------

Protection and monitoring

Output overvoltage protection	Additional control loop, limitation (closed loop control) at < 28.8 V
Current limitation	3.15 ... 3.6 A
Current limitation, typ.	3.4 A
property of the output short-circuit proof	Yes
Short-circuit protection	Electronic shutdown, automatic restart
Overload/short-circuit indicator	-

Safety

Primary/secondary isolation	Yes
galvanic isolation	Safety extra-low output voltage U _{out} acc. to EN 60950-1 and EN 50178 and EN 61131-2
Protection class	Class I
leakage current	
• maximum	3.5 mA
• typical	0.4 mA
Degree of protection (EN 60529)	IP20

Approvals

CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 142), File E143289
Explosion protection	IECEX Ex nA nC IIC T4 Gc; ATEX (EX) II 3G Ex nA nC IIC T4 Gc; cULus (ANSI/ISA 12.12.01, CSA C22.2 No.213) Class I, Div. 2, Group ABCD, T4, File E330455
certificate of suitability NEC Class 2	No
FM approval	Class I, Div. 2, Group ABCD, T4
CB approval	Yes
Marine approval	ABS, BV, DNV GL

EMC

Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

environmental conditions

ambient temperature	
• during operation	0 ... 60 °C
— Note	with natural convection
• during transport	-40 ... +85 °C
• during storage	-40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, 5 ... 95% no condensation

Mechanics

Connection technology	Screw-/spring clamp connection
Connections	

<ul style="list-style-type: none"> • Supply input • Output 	L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm ² L+, M: 2 spring-loaded terminals each for 0.5 to 2.5 mm ²
product function	
<ul style="list-style-type: none"> • removable terminal at input • removable terminal at output 	Yes Yes
width of the enclosure	50 mm
height of the enclosure	147 mm
depth of the enclosure	129 mm
required spacing	
<ul style="list-style-type: none"> • top • bottom • left • right 	40 mm 40 mm 0 mm 0 mm
Weight, approx.	0.45 kg
product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Can be mounted onto S7-1500 rail
MTBF at 40 °C	1 611 993 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)