

SITOP SMART/1AC/24VDC/10A/WALL MOUNTING

SITOP smart 240 W Stabilized power supply input: 120/230 V AC, output: DC 24 V/10 A Option for for wall mounting

Input	
type of the power supply network	1-phase AC
supply voltage at AC	Set by means of selector switch on the device
<ul style="list-style-type: none"> initial value 	
supply voltage	120 V 230 V
<ul style="list-style-type: none"> 1 at AC rated value 2 at AC rated value 	
input voltage	85 ... 132 V 170 ... 264 V
<ul style="list-style-type: none"> 1 at AC 2 at AC 	
design of input wide range input	No
overvoltage overload capability	$2.3 \times V_{in}$ rated, 1.3 ms
operating condition of the mains buffering	at $V_{in} = 93/187$ V
buffering time for rated value of the output current in the event of power failure minimum	20 ms
operating condition of the mains buffering	at $V_{in} = 93/187$ V
line frequency	50 Hz 60 Hz
<ul style="list-style-type: none"> 1 rated value 2 rated value 	
line frequency	47 ... 63 Hz
input current	4.1 A 2.4 A
<ul style="list-style-type: none"> at rated input voltage 120 V at rated input voltage 230 V 	
current limitation of inrush current at 25 °C maximum	65 A
duration of inrush current limiting at 25 °C	3 ms
<ul style="list-style-type: none"> typical 	
I ² t value maximum	3.3 A ² ·s
fuse protection type	T 6.3 A/250 V (not accessible)
<ul style="list-style-type: none"> in the feeder 	Recommended miniature circuit breaker: from 10 A characteristic C
Output	
voltage curve at output	Controlled, isolated DC voltage
output voltage at DC rated value	24 V
output voltage	24 V
<ul style="list-style-type: none"> at output 1 at DC rated value 	
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	0.1 % 0.5 %
<ul style="list-style-type: none"> on slow fluctuation of input voltage on slow fluctuation of ohm loading 	
residual ripple	150 mV 50 mV
<ul style="list-style-type: none"> maximum typical 	
voltage peak	240 mV 150 mV
<ul style="list-style-type: none"> maximum typical 	
adjustable output voltage	22.8 ... 28 V
product function output voltage adjustable	Yes
type of output voltage setting	via potentiometer
display version for normal operation	Green LED for 24 V OK
behavior of the output voltage when switching on	Overshoot of V_{out} approx. 4 %

response delay maximum	0.1 s
voltage increase time of the output voltage	
• typical	50 ms
output current	
• rated value	10 A
• rated range	0 ... 12 A; 12 A up to +45 °C
supplied active power typical	288 W
short-term overload current	
• on short-circuiting during the start-up typical	30 A
• at short-circuit during operation typical	33 A
duration of overloading capability for excess current	
• on short-circuiting during the start-up	100 ms
• at short-circuit during operation	200 ms
product feature	
• bridging of equipment	Yes
number of parallel-switched equipment resources for increasing the power	2
Efficiency	
efficiency in percent	90 %
power loss [W]	
• at rated output voltage for rated value of the output current typical	27 W
Closed-loop control	
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	0.3 %
relative control precision of the output voltage load step of resistive load 50/100/50 % typical	1 %
setting time	
• load step 50 to 100% typical	0.2 ms
• load step 100 to 50% typical	0.2 ms
Protection and monitoring	
design of the overvoltage protection	< 33 V
response value current limitation	12.5 ... 13.5 A
property of the output short-circuit proof	Yes
design of short-circuit protection	Constant current characteristic
enduring short circuit current RMS value	
• typical	16 A
display version for overload and short circuit	-
Safety	
galvanic isolation between input and output	Yes
galvanic isolation	Safety extra-low output voltage Uout acc. to EN 60950-1 and EN 50178
operating resource protection class	Class I
leakage current	
• maximum	3.5 mA
• typical	0.8 mA
protection class IP	IP20
Approvals	
certificate of suitability	
• CE marking	Yes
• UL approval	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
• CSA approval	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
• cCSAus, Class 1, Division 2	No
• ATEX	No
certificate of suitability	
• IECEX	No
• NEC Class 2	No
• ULhazloc approval	No
• FM registration	No
type of certification CB-certificate	Yes
certificate of suitability	

• EAC approval	Yes
certificate of suitability shipbuilding approval	Yes
shipbuilding approval	DNV GL
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	No
• French marine classification society (BV)	No
• DNV GL	Yes
• Lloyds Register of Shipping (LRS)	No
• Nippon Kaiji Kyokai (NK)	No
EMC	
standard	
• for emitted interference	EN 55022 Class B
• for mains harmonics limitation	-
• for interference immunity	EN 61000-6-2
environmental conditions	
ambient temperature	
• during operation	0 ... 60 °C; with natural convection
• during transport	-40 ... +85 °C
• during storage	-40 ... +85 °C
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
Mechanics	
type of electrical connection	screw-type terminals
• at input	L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm ² single-core/finely stranded
• at output	L+, M: 2 screw terminals each for 0.5 ... 2.5 mm ²
• for auxiliary contacts	-
width of the enclosure	70 mm
height of the enclosure	125 mm
depth of the enclosure	125 mm
required spacing	
• top	50 mm
• bottom	50 mm
• left	0 mm
• right	0 mm
net weight	0.85 kg
product feature of the enclosure housing can be lined up	Yes
fastening method	Wall mounting
MTBF at 40 °C	1 460 803 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

