



Figure similar

SITOP PSE200U/4X3-10A/CSC

SITOP PSE200U 10 A Selectivity module 4-channel input: 24 V DC/40 A output: 24 V DC/4x 10 A Level adjustable 3-10 A with common signaling contact

Input	
type of the power supply network	Controlled DC voltage
supply voltage / at DC / rated value	24 V
input voltage / at DC	22 ... 30 V
overvoltage overload capability	35 V
input current / at rated input voltage 24 V / rated value	40 A
Output	
voltage curve / at output	controlled DC voltage
formula for output voltage	$V_{in} - \text{approx. } 0.2 \text{ V}$
relative overall tolerance / of the voltage / note	In accordance with the supplying input voltage
number of outputs	4
output current / up to 60 °C / per output / rated value	10 A
adjustable current response value current / of the current-dependent overload release	3 ... 10 A
type of response value setting	via potentiometer
product feature	
<ul style="list-style-type: none"> <li>parallel switching of outputs</li> <li>bridging of equipment</li> </ul>	<p>No</p> <p>Yes</p>
type of outputs connection	Simultaneous connection of all outputs after power up of the supply voltage > 20 V, delay time of 25 ms, 100 ms or adjustable "load optimised" via DIP switch for sequential connection
Efficiency	
efficiency in percent	99 %
power loss [W] / at rated output voltage / for rated value of the output current / typical	10 W
Switch-off characteristic per output	
switching characteristic	
<ul style="list-style-type: none"> <li>of the excess current</li> <li>of the current limitation</li> <li>of the immediate switch-off</li> </ul>	<p><math>I_{out} = 1.0 \dots 1.5 \times \text{set value}</math>, switch-off after approx. 5 s</p> <p><math>I_{out} = 1.5 \times \text{set value}</math>, switch-off after typ. 100 ms</p> <p><math>I_{out} &gt; \text{set value}</math> and <math>V_{in} &lt; 20 \text{ V}</math>, switch-off after approx. 0.5 ms</p>
residual current at switch-off / typical	1 mA
design of the reset device/resetting mechanism	via sensor per output
remote reset function	Non-electrically isolated 24 V input (signal level "high" at > 15 V)
Protection and monitoring	
fuse protection type / at input	15 A per output (not accessible)
display version / for normal operation	Three-color LED per output: green LED for "Output switched through"; yellow LED for "Output switched off manually"; red LED for "Output switched off due to overcurrent"

design of the switching contact / for signaling function	Common signal contact (changeover contact, rating 0.1 A/24 V DC)
<b>Safety</b>	
galvanic isolation / between input and output at switch-off standard / for safety	No according to EN 60950-1 and EN 50178
operating resource protection class	Class III
protection class IP	IP20
<b>Approvals</b>	
certificate of suitability <ul style="list-style-type: none"> <li>• CE marking</li> <li>• UL approval</li> <li>• ATEX</li> </ul>	Yes Yes; UL-Recognized (UL 2367) File E328600; cULus-Listed (UL 508, CSA C22.2 No. 107.1) File E197259 Yes; IECEx Ex nA nC IIC T4 Gc; ATEX (EX) II 3G Ex nA nC IIC T4 Gc; cULus Class I, Div. 2, Group ABCD, T4
standard / for explosion protection	IECEX (IEC 60079-0, -15); ATEX (EN 60079-0, -15); cULus (UL 121201, CSA C22.2 No. 213-17)
certificate of suitability <ul style="list-style-type: none"> <li>• IECEx</li> <li>• shipbuilding approval</li> </ul>	Yes Yes
shipbuilding approval	DNV GL, ABS
Marine classification association <ul style="list-style-type: none"> <li>• American Bureau of Shipping Europe Ltd. (ABS)</li> <li>• DNV GL</li> </ul>	Yes Yes
<b>EMC</b>	
standard <ul style="list-style-type: none"> <li>• for emitted interference</li> <li>• for interference immunity</li> </ul>	EN 55022 Class B EN 61000-6-2
<b>environmental conditions</b>	
ambient temperature <ul style="list-style-type: none"> <li>• during operation</li> <li>• during transport</li> <li>• during storage</li> </ul>	-25 ... +60 °C; with natural convection -40 ... +85 °C -40 ... +85 °C
environmental category / acc. to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
<b>Mechanics</b>	
type of electrical connection <ul style="list-style-type: none"> <li>• at input</li> <li>• at output</li> <li>• for signaling contact</li> <li>• for auxiliary contacts</li> </ul>	screw-type terminals +24 V: 2 screw terminals for 0.5 ... 16 mm <sup>2</sup> ; 0 V: 2 screw terminals for 0.5 ... 4 mm <sup>2</sup> Output 1 ... 4: 1 screw terminal each for 0.5 ... 4 mm <sup>2</sup> 3 screw terminals for 0.5 ... 4 mm <sup>2</sup> Remote reset: 1 screw terminal for 0.5 ... 4 mm <sup>2</sup>
width / of the enclosure	72 mm
height / of the enclosure	80 mm
depth / of the enclosure	72 mm
installation width	72 mm
mounting height	180 mm
required spacing <ul style="list-style-type: none"> <li>• top</li> <li>• bottom</li> <li>• left</li> <li>• right</li> </ul>	50 mm 50 mm 0 mm 0 mm
net weight	0.2 kg
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
mechanical accessories	Device identification label 20 mm × 7 mm, TI-grey 3RT2900-1SB20
MTBF / at 40 °C	540 979 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

