



*** Spare part *** SIMATIC DP, 5 electronic modules for ET 200S, 4 DI source input 24 V DC, 15 mm width 5 units per packing unit

Supply voltage	
Rated value (DC)	24 V; From power module
Reverse polarity protection	Yes
Input current	
from supply voltage L+, max.	Dependent on encoder
Encoder supply	
Type of output voltage	max. M +0.5 V, under load
Output current	
<ul style="list-style-type: none"> Rated value permissible range, lower limit permissible range, upper limit 	500 mA 0 mA 500 mA
Power loss	
Power loss, typ.	0.7 W
Address area	
Address space per module	<ul style="list-style-type: none"> Address space per module, max. with packing
	1 byte 4 bit
Digital inputs	
Number of digital inputs	4
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input voltage	
<ul style="list-style-type: none"> Type of input voltage Rated value (DC) for signal "0" for signal "1" 	DC 24 V -5 to +30V -15 to -30 V
Input current	
<ul style="list-style-type: none"> for signal "1", typ. 	7 mA; at 24 V
Input delay (for rated value of input voltage)	
for standard inputs	
<ul style="list-style-type: none"> parameterizable at "0" to "1", min. at "0" to "1", max. at "1" to "0", min. at "1" to "0", max. 	No 2 ms; typically 3 ms 4.5 ms 2 ms; typically 3 ms 4.5 ms
Cable length	
<ul style="list-style-type: none"> shielded, max. unshielded, max. 	1 000 m 600 m
Encoder	

Connectable encoders	
<ul style="list-style-type: none"> • 2-wire sensor <ul style="list-style-type: none"> — permissible quiescent current (2-wire sensor), max. 	Yes 1.5 mA
Interrupts/diagnostics/status information	
Diagnostics function	No
Diagnostics indication LED	
<ul style="list-style-type: none"> • Group error SF (red) • Status indicator digital input (green) 	No Yes; per channel
Parameter	
Remark	1 byte
Potential separation	
Potential separation digital inputs	
<ul style="list-style-type: none"> • between the channels • between the channels and backplane bus 	No Yes
Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	35 g
last modified:	5/27/2021 