



*** Spare part *** SIMATIC DP, 5 electronic modules for ET 200S, 4 DO sink output 24 V DC/0.5 A, 15 mm width 5 units per packing unit

Supply voltage	
Reverse voltage protection	Yes; when using the same load voltage as on the power module
Load voltage L+	
<ul style="list-style-type: none"> Rated value (DC) Reverse polarity protection 	24 V; From power module Yes
Input current	
from load voltage L+ (without load), max.	5 mA; Per channel
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	0.8 W
Address area	
Address space per module	
<ul style="list-style-type: none"> Address space per module, max. with packing 	1 byte 4 bit
Digital outputs	
Type of digital output	Transistor
Number of digital outputs	4
Short-circuit protection	Yes
Controlling a digital input	Yes
Switching capacity of the outputs	
<ul style="list-style-type: none"> on lamp load, max. 	5 W
Load resistance range	
<ul style="list-style-type: none"> lower limit upper limit 	48 Ω 3 400 Ω
Output voltage	
<ul style="list-style-type: none"> for signal "1", min. 	1 V
Output current	
<ul style="list-style-type: none"> for signal "1" rated value for signal "1" permissible range, min. for signal "1" permissible range, max. for signal "0" residual current, max. 	0.5 A 5 mA 600 mA 5 μA
Output delay with resistive load	
<ul style="list-style-type: none"> "0" to "1", max. "1" to "0", max. 	300 μs 600 μs
Parallel switching of two outputs	
<ul style="list-style-type: none"> for uprating for redundant control of a load 	No Yes; per module
Switching frequency	
<ul style="list-style-type: none"> with resistive load, max. 	100 Hz

<ul style="list-style-type: none"> with inductive load, max. 	0.5 Hz
<ul style="list-style-type: none"> on lamp load, max. 	10 Hz
Total current of the outputs	
<ul style="list-style-type: none"> Current per module, max. 	2 A
Cable length	
<ul style="list-style-type: none"> shielded, max. 	1 000 m
<ul style="list-style-type: none"> unshielded, max. 	600 m
Interrupts/diagnostics/status information	
Diagnostics function	No
Diagnostics indication LED	
<ul style="list-style-type: none"> Status indicator digital output (green) 	Yes
Parameter	
Remark	1 byte
Potential separation	
Potential separation digital outputs	
<ul style="list-style-type: none"> between the channels 	No
<ul style="list-style-type: none"> between the channels and backplane bus 	Yes
Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	40 g
last modified:	5/24/2021 