



Figure similar

SIMATIC DP, Electronics module for ET 200S, 2 AI Standard U 15 mm width, +/-10V; 13 bit+sign +/-5 V; 12 bit+sign, 1..5 V; 12-bit Cycle time 65 ms/channel with SF LED (group fault)

General information	
Product function	
<ul style="list-style-type: none"> • Isochronous mode 	No
Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> • Rated value (DC) • Reverse polarity protection 	24 V; From power module Yes
Input current	
from load voltage L+ (without load), max.	30 mA
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	0.6 W
Address area	
Address space per module	
<ul style="list-style-type: none"> • Address space per module, max. 	4 byte
Analog inputs	
Number of analog inputs	2
permissible input voltage for voltage input (destruction limit), max.	35 V; 35 V continuous; 75 V for max. 1 ms (mark to space ratio 1:20)
Cycle time (all channels) max.	Number of active channels per module x basic conversion time
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> • 1 V to 5 V • -10 V to +10 V • -5 V to +5 V 	Yes Yes Yes
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	200 m
Analog value generation for the inputs	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> • Resolution with overrange (bit including sign), max. • Integration time, parameterizable • Integration time (ms) • Interference voltage suppression for interference frequency f1 in Hz • Conversion time (per channel) 	14 bit; ±10 V: 13 bit + sign, ±5 V: 13 bit + sign; 1 to 5 V: 13 bit Yes 16,7 / 20 ms 50 / 60 Hz 65 ms; 55 / 65 ms
Smoothing of measured values	
<ul style="list-style-type: none"> • parameterizable • Step: None • Step: low • Step: Medium 	Yes; In four stages by means of digital filtering Yes; 1x cycle time Yes; 4x cycle time Yes; 32x cycle time

• Step: High	Yes; 64x cycle time
Errors/accuracies	
Operational error limit in overall temperature range	
• Voltage, relative to input range, (+/-)	0.6 %
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to input range, (+/-)	0.4 %
Interrupts/diagnostics/status information	
Diagnoses	
• Wire-break	Yes; Measuring range 1 to 5 V only
• Group error	Yes
• Overflow/underflow	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
Parameter	
Remark	4 byte
Diagnostics wire break	Disable / enable (only in measuring range 1 to 5 V)
Group diagnostics	Disable / enable
Overflow/underflow	Disable / enable
Potential separation	
Potential separation analog inputs	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes
Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	40 g
last modified:	2/9/2021 