



SIMATIC DP, Electronics module for ET 200S, 2 AO U High Speed, 15 mm width, +/-10 V, +/-5 V, 1.. 5V; 16 bit, Cycle time: 0.1ms with SF LED (group fault)

General information	
Product function	
<ul style="list-style-type: none"> • Isochronous mode 	Yes
Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> • Rated value (DC) 	24 V; From power module
<ul style="list-style-type: none"> • Reverse polarity protection 	Yes
Input current	
from load voltage L+ (without load), max.	130 mA
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	2.2 W
Address area	
Address space per module	
<ul style="list-style-type: none"> • Address space per module, max. 	4 byte
Analog outputs	
Number of analog outputs	2
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	25 mA
Cycle time (all channels) max.	0.25 ms
Output ranges, voltage	
<ul style="list-style-type: none"> • 1 V to 5 V 	Yes
<ul style="list-style-type: none"> • -5 V to +5 V 	Yes
<ul style="list-style-type: none"> • -10 V to +10 V 	Yes
Connection of actuators	
<ul style="list-style-type: none"> • for voltage output two-wire connection 	Yes; Without compensation of the line resistances
<ul style="list-style-type: none"> • for voltage output four-wire connection 	Yes
Load impedance (in rated range of output)	
<ul style="list-style-type: none"> • with voltage outputs, min. 	1 kΩ
<ul style="list-style-type: none"> • with voltage outputs, capacitive load, max. 	1 μF; 0.1 μF for Twa=0.1 ms
Destruction limits against externally applied voltages and currents	
<ul style="list-style-type: none"> • Voltages at the outputs towards MANA 	15 V; Max. 15 V for max. 5 hours, 75 V for max. 1 s
<ul style="list-style-type: none"> • Current, max. 	30 mA; DC
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	200 m; Max. 20 m for TWA 100 μs
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> • Resolution with overrange (bit including sign), max. 	16 bit; 1 to 5 V: 14 bit, ±10 V: 15 bit + sign, ±5 V: 14 bit + sign
Settling time	

• for resistive load	0.05 ms
• for capacitive load	0.05 ms
• for inductive load	0.05 ms
Errors/accuracies	
Operational error limit in overall temperature range	
• Voltage, relative to output range, (+/-)	0.2 %
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to output range, (+/-)	0.01 %
Interrupts/diagnostics/status information	
Diagnoses	
• Diagnostic information readable	Yes
• Wire-break	No
• Short-circuit	Yes
• Group error	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
Parameter	
Remark	7 byte
Diagnostics short-circuit	Disable / enable
Group diagnostics	Disable / enable
Response to CPU/master STOP	Output current and de-energized/substitute a value/keep last value
Potential separation	
Potential separation analog outputs	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes
Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	40 g
last modified:	1/16/2021 