



Figure similar

\*\*\* spare part \*\*\* ET 200S Compact, 16 DI/16 DQ STD 24 V DC, 3 ms.; 24 V DC, 0.5 A expandable by up to 12 modules of the ET 200S (no F modules) electronics block

General information	
Vendor identification (VendorID)	8200H
Product function	
• Isochronous mode	No
Supply voltage	
Load voltage 1L+	
• Rated value (DC)	24 V
• Reverse polarity protection	Yes
Input current	
from supply voltage 1L+, max.	100 mA
Power loss	
Power loss, typ.	3 W
Address area	
Addressing volume	
• Inputs	100 byte
• Outputs	100 byte
Digital inputs	
Number of digital inputs	16
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	-30 to +5 V
• for signal "1"	13 to 30V
Input current	
• for signal "1", typ.	3 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", min.	1.2 ms; typically 3 ms
— at "0" to "1", max.	4.8 ms; typically 3 ms
— at "1" to "0", min.	1.2 ms; typically 3 ms
— at "1" to "0", max.	4.8 ms; typically 3 ms
Cable length	
• unshielded, max.	1 000 m
Digital outputs	
Number of digital outputs	16
Short-circuit protection	Yes
Limitation of inductive shutdown voltage to	L+ (-55 to -60 V)
Controlling a digital input	Yes

<b>Switching capacity of the outputs</b>	
• on lamp load, max.	5 W
<b>Output voltage</b>	
• for signal "1", min.	L+ (-0.8 V)
<b>Output current</b>	
• for signal "1" permissible range, min.	7 mA
• for signal "1" permissible range, max.	0.6 A
• for signal "0" residual current, max.	0.5 mA
<b>Output delay with resistive load</b>	
• "0" to "1", max.	0.5 ms
• "1" to "0", max.	1.3 ms
<b>Switching frequency</b>	
• with resistive load, max.	100 Hz
• with inductive load, max.	2 Hz
• on lamp load, max.	10 Hz
<b>Total current of the outputs (per group)</b>	
all mounting positions	
— up to 60 °C, max.	2 A
<b>Cable length</b>	
• unshielded, max.	1 000 m
<b>Encoder</b>	
<b>Connectable encoders</b>	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
<b>1. Interface</b>	
<b>Interface types</b>	
• RS 485	Yes
• Output current of the interface, max.	80 mA
<b>Interface types</b>	
<b>RS 485</b>	
• Transmission rate, max.	12 Mbit/s
• Cable length, max.	1 200 m
<b>Protocols</b>	
Supports protocol for PROFINET IO	No
PROFIBUS DP	Yes
<b>Protocols (Ethernet)</b>	
• TCP/IP	No
<b>PROFIBUS DP</b>	
<b>Services</b>	
— Direct data exchange (slave-to-slave communication)	Yes
<b>Interrupts/diagnostics/status information</b>	
Alarms	No
Diagnostics function	Yes
<b>Diagnostics indication LED</b>	
• Bus fault BF (red)	Yes
• Group error SF (red)	Yes
• Status indicator digital input (green)	Yes
• Status indicator digital output (green)	Yes
• Monitoring 24 V voltage supply ON (green)	Yes
<b>Potential separation</b>	
between backplane bus and electronics	No
between supply voltage and electronics	No
<b>Potential separation digital inputs</b>	
• Potential separation digital inputs	No
<b>Potential separation digital outputs</b>	
• Potential separation digital outputs	Yes
<b>Isolation</b>	
Isolation tested with	500 V DC

Degree and class of protection	
IP degree of protection	IP20
connection method / header	
Design of electrical connection for the inputs and outputs	Screw-type and spring-loaded terminals, permanent wiring; 3 and 4-wire connection
Dimensions	
Width	120 mm
Height	81 mm
Depth	58 mm
Weights	
Weight, approx.	230 g; EB only
<b>last modified:</b>	10/3/2021 