

SIMATIC S7-300, Digital module SM 323, isolated, 16 DI and 16 DO, 24 V DC, 0.5 A, Total current 4A, 1x 40-pole



Figure similar

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
Input current	
from load voltage L+ (without load), max.	80 mA
from backplane bus 5 V DC, max.	80 mA
Power loss	
Power loss, typ.	6.5 W
Digital inputs	
Number of digital inputs	16
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
horizontal installation	

— up to 40 °C, max.	16
— up to 60 °C, max.	8
<b>vertical installation</b>	
— up to 40 °C, max.	16
<b>Input voltage</b>	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	-30 to +5 V
• for signal "1"	13 to 30V
<b>Input current</b>	
• for signal "1", typ.	7 mA
<b>Input delay (for rated value of input voltage)</b>	
<b>for standard inputs</b>	
— at "0" to "1", min.	1.2 ms
— at "0" to "1", max.	4.8 ms
— at "1" to "0", min.	1.2 ms
— at "1" to "0", max.	4.8 ms
<b>Cable length</b>	
• shielded, max.	1 000 m
• unshielded, max.	600 m
<b>Digital outputs</b>	
Number of digital outputs	16
Short-circuit protection	Yes
• Response threshold, typ.	1 A
Limitation of inductive shutdown voltage to	L+ (-48 V)
Controlling a digital input	Yes
<b>Switching capacity of the outputs</b>	
• on lamp load, max.	5 W
<b>Load resistance range</b>	
• lower limit	48 Ω
• upper limit	4 kΩ
<b>Output voltage</b>	
• for signal "1", min.	L+ (-0.8 V)
<b>Output current</b>	
• for signal "1" rated value	0.5 A
• for signal "1" permissible range, min.	5 mA
• for signal "1" permissible range, max.	0.6 A
• for signal "1" minimum load current	5 mA
• for signal "0" residual current, max.	0.5 mA
<b>Output delay with resistive load</b>	
• "0" to "1", max.	100 μs

<ul style="list-style-type: none"> <li>• "1" to "0", max.</li> </ul>	500 $\mu$ s
<b>Parallel switching of two outputs</b>	
<ul style="list-style-type: none"> <li>• for uprating</li> </ul>	No
<ul style="list-style-type: none"> <li>• for redundant control of a load</li> </ul>	Yes; only outputs of the same group
<b>Switching frequency</b>	
<ul style="list-style-type: none"> <li>• with resistive load, max.</li> </ul>	100 Hz
<ul style="list-style-type: none"> <li>• with inductive load, max.</li> </ul>	0.5 Hz
<ul style="list-style-type: none"> <li>• on lamp load, max.</li> </ul>	100 Hz
<b>Total current of the outputs (per group)</b>	
<b>horizontal installation</b>	
— up to 40 °C, max.	4 A
— up to 60 °C, max.	3 A
<b>vertical installation</b>	
— up to 40 °C, max.	2 A
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>	1 000 m
<ul style="list-style-type: none"> <li>• unshielded, max.</li> </ul>	600 m
<b>Encoder</b>	
<b>Connectable encoders</b>	
<ul style="list-style-type: none"> <li>• 2-wire sensor</li> </ul>	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
<b>Interrupts/diagnostics/status information</b>	
Alarms	No
Diagnostics function	No
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>• Status indicator digital input (green)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Status indicator digital output (green)</li> </ul>	Yes
<b>Potential separation</b>	
<b>Potential separation digital inputs</b>	
<ul style="list-style-type: none"> <li>• between the channels</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• between the channels, in groups of</li> </ul>	16
<ul style="list-style-type: none"> <li>• between the channels and backplane bus</li> </ul>	Yes; Optocoupler
<b>Potential separation digital outputs</b>	
<ul style="list-style-type: none"> <li>• between the channels</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• between the channels, in groups of</li> </ul>	8
<ul style="list-style-type: none"> <li>• between the channels and backplane bus</li> </ul>	Yes; Optocoupler
<b>Isolation</b>	
Isolation tested with	500 V DC
<b>Connection method</b>	

required front connector	40-pin
<b>Dimensions</b>	
Width	40 mm
Height	125 mm
Depth	120 mm
<b>Weights</b>	
Weight, approx.	260 g
<b>last modified:</b>	10/07/2020