



SIMATIC S7-400, analog input SM 431, isolated 8 AI, resolution 14 bit, U/I/Resistor/Thermocouple/Pt100

Figure similar

Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> Rated value (DC) Reverse polarity protection 	24 V; Only required for supplying 2-wire transmitters Yes
Input current	
from load voltage L+ (without load), max.	200 mA; for 8 connected, fully controlled 2-wire transmitters
from backplane bus 5 V DC, max.	600 mA
Power loss	
Power loss, typ.	3.5 W
Analog inputs	
Number of analog inputs	8
<ul style="list-style-type: none"> For voltage/current measurement For resistance measurement 	8 4
permissible input voltage for voltage input (destruction limit), max.	18 V; 18 V continuous, 75 V for 1 ms (mark to space ratio 1:20)
permissible input current for current input (destruction limit), max.	40 mA; Permanent
Constant measurement current for resistance-type transmitter, typ.	1.67 mA
Input ranges	
<ul style="list-style-type: none"> Voltage Current Thermocouple Resistance thermometer Resistance 	Yes Yes Yes Yes Yes
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> 1 V to 5 V <ul style="list-style-type: none"> Input resistance (1 V to 5 V) -1 V to +1 V <ul style="list-style-type: none"> Input resistance (-1 V to +1 V) -10 V to +10 V <ul style="list-style-type: none"> Input resistance (-10 V to +10 V) -2.5 V to +2.5 V <ul style="list-style-type: none"> Input resistance (-2.5 V to +2.5 V) -250 mV to +250 mV <ul style="list-style-type: none"> Input resistance (-250 mV to +250 mV) -5 V to +5 V 	Yes 1 MΩ Yes 1 MΩ Yes 1 MΩ Yes 1 MΩ Yes 1 MΩ Yes

— Input resistance (-5 V to +5 V)	1 M Ω
• -500 mV to +500 mV	Yes
— Input resistance (-500 mV to +500 mV)	1 M Ω
• -80 mV to +80 mV	Yes
— Input resistance (-80 mV to +80 mV)	1 M Ω
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	50 Ω
• 4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	50 Ω
Input ranges (rated values), thermocouples	
• Type B	Yes
— Input resistance (Type B)	1 M Ω
• Type E	Yes
— Input resistance (Type E)	1 M Ω
• Type J	Yes
— Input resistance (type J)	1 M Ω
• Type K	Yes
— Input resistance (Type K)	1 M Ω
• Type L	Yes
— Input resistance (Type L)	1 M Ω
• Type N	Yes
— Input resistance (Type N)	1 M Ω
• Type R	Yes
— Input resistance (Type R)	1 M Ω
• Type S	Yes
— Input resistance (Type S)	1 M Ω
• Type T	Yes
— Input resistance (Type T)	1 M Ω
• Type U	Yes
— Input resistance (Type U)	1 M Ω
Input ranges (rated values), resistance thermometer	
• Ni 100	Yes
— Input resistance (Ni 100)	1 M Ω
• Ni 1000	Yes
— Input resistance (Ni 1000)	1 M Ω
• Pt 100	Yes
— Input resistance (Pt 100)	1 M Ω
• Pt 1000	Yes
• Pt 10000	Yes
• Pt 200	Yes
— Input resistance (Pt 200)	1 M Ω
• Pt 500	Yes
— Input resistance (Pt 500)	1 M Ω
Input ranges (rated values), resistors	
• 0 to 48 ohms	Yes
— Input resistance (0 to 48 ohms)	1 M Ω
• 0 to 150 ohms	Yes
— Input resistance (0 to 150 ohms)	1 M Ω
• 0 to 300 ohms	Yes
— Input resistance (0 to 300 ohms)	1 M Ω
• 0 to 600 ohms	Yes
— Input resistance (0 to 600 ohms)	1 M Ω
• 0 to 6000 ohms	Yes; Usable up to 5000 Ohm
— Input resistance (0 to 6000 ohms)	1 M Ω
Thermocouple (TC)	
Temperature compensation	
— parameterizable	Yes

— internal temperature compensation	No
— external temperature compensation with Pt100	Yes
— external temperature compensation with compensations socket	Yes
— dynamic reference temperature value	Yes
Characteristic linearization	
• parameterizable	Yes
— for thermocouples	Type B, E, J, K, L, N, R, S, T, U
— for resistance thermometer	Pt100, Pt200, Pt500, Pt1000, Ni100, Ni1000
Cable length	
• shielded, max.	200 m; 50 m with thermocouples and input ranges ≤ 80 mV
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	14 bit; with activated filtering: 16 bit
• Integration time, parameterizable	Yes
• Basic conversion time (ms)	20.1 / 23.5 ms
Encoder	
Connection of signal encoders	
• for voltage measurement	Yes; possible
• for current measurement as 2-wire transducer	Yes
• for current measurement as 4-wire transducer	Yes
• for resistance measurement with two-wire connection	Yes; Line resistances are also measured
• for resistance measurement with three-wire connection	Yes
• for resistance measurement with four-wire connection	Yes
Errors/accuracies	
Operational error limit in overall temperature range	
• Voltage, relative to input range, (+/-)	0.38 %; ± 0.38 % at ± 80 mV; ± 0.35 % at ± 250 mV, ± 500 mV, ± 1 V, ± 2.5 V, ± 5 V, 1 to 5 V, ± 10 V
• Current, relative to input range, (+/-)	0.35 %; ± 20 mA, 0 to 20 mA, 4 to 20 mA
• Resistance, relative to input range, (+/-)	0.5 %
• Resistance thermometer, relative to input range, (+/-)	0.5 %
• Thermocouple, relative to input range, (+/-)	TC Type B (± 14.8 K), TC Type R (± 9.4 K), TC Type S (± 10.6 K), TC Type T (± 2.2 K), TC Type E (± 4.0 K), TC Type J (± 5.2 K), TC Type K (± 7.6 K), TC Type U (± 3.5 K), TC Type L (± 5.1 K), TC Type N (± 5.5 K)
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to input range, (+/-)	0.15 %; ± 0.15 % (± 250 mV, ± 500 mV, ± 1 V, ± 2.5 V, ± 5 V, 1 to 5 V, ± 10 V); ± 0.17 % (± 80 mV)
• Current, relative to input range, (+/-)	0.15 %; ± 20 mA, 0 to 20 mA, 4 to 20 mA
• Resistance, relative to input range, (+/-)	0.15 %; ± 0.15 % at 0 to 48 ohms (4-conductor measurement), 0 to 150 ohms (4-conductor measurement), 0 to 300 ohms (4-conductor measurement), 0 to 600 ohms (4-conductor measurement), 0 to 5000 ohms (4-conductor measurement, in range of 6000 ohms); ± 0.3 % at 0 to 300 ohms (3-conductor measurement), 0 to 600 ohms (3-conductor measurement), 0 to 5000 ohms (3-conductor measurement, in range of 6000 ohms)
• Resistance thermometer, relative to input range, (+/-)	0.3 %
• Thermocouple, relative to input range, (+/-)	TC Type B (± 8.2 K), TC Type R (± 5.2 K), TC Type S (± 5.9 K), TC Type T (± 1.2 K), TC Type E (± 1.8 K), TC Type J (± 2.3 K), TC Type K (± 3.4 K), TC Type U (± 1.8 K), TC Type L (± 2.3 K), TC Type N (± 2.9 K)
Interrupts/diagnostics/status information	
Diagnostics function	No
Potential separation	
Potential separation analog inputs	
• Potential separation analog inputs	Yes; internal/external
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes

Isolation	
Isolation tested with	2 120 V DC between bus and L+/M; 2 120 V DC between bus and analog section; 500 V DC between bus and local ground; 500 V DC between analog section and L+/M; 2 120 V DC between analog section and local ground; 2 120 V DC between L+/M and local ground
Dimensions	
Width	25 mm
Height	290 mm
Depth	210 mm
Weights	
Weight, approx.	500 g
last modified:	3/2/2021 