

SIMATIC S7-1500, digital output module DQ16x24 V DC/0.5 A HF; 16 channels in groups of 8; 4 A per group; Single-channel diagnostics; Substitute value: Front connector (screw terminals or push-in) to be ordered separately



General information	
Product type designation	DQ 16x24VDC/0.5A HF
HW functional status	From FS02
Firmware version	V1.1.0
<ul style="list-style-type: none"> FW update possible 	Yes
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> Isochronous mode 	Yes
<ul style="list-style-type: none"> Prioritized startup 	Yes
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version 	V13 SP1 / -
<ul style="list-style-type: none"> PROFIBUS from GSD version/GSD revision 	V1.0 / V5.1
<ul style="list-style-type: none"> PROFINET from GSD version/GSD revision 	V2.3 / -
Operating mode	
<ul style="list-style-type: none"> DQ 	Yes
<ul style="list-style-type: none"> DQ with energy-saving function 	No
<ul style="list-style-type: none"> PWM 	No
<ul style="list-style-type: none"> Cam control (switching at comparison values) 	No

• Oversampling	No
• MSO	Yes
• Integrated operating cycle counter	Yes

Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes; through internal protection with 7 A per group

Input current

Current consumption, max.	30 mA
---------------------------	-------

Output voltage

Rated value (DC)	24 V
------------------	------

Power

Power available from the backplane bus	1.1 W
--	-------

Power loss

Power loss, typ.	2 W
------------------	-----

Digital outputs

Type of digital output	Transistor
Number of digital outputs	16
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
Short-circuit protection	Yes; Clocked electronically
• Response threshold, typ.	1 A
Limitation of inductive shutdown voltage to	L+ (-53 V)
Controlling a digital input	Yes

Switching capacity of the outputs

• with resistive load, max.	0.5 A
• on lamp load, max.	5 W

Load resistance range

• lower limit	48 Ω
• upper limit	12 k Ω

Output voltage

• for signal "1", min.	L+ (-0.8 V)
------------------------	-------------

Output current

• for signal "1" rated value	0.5 A
• for signal "1" permissible range, max.	0.5 A
• for signal "0" residual current, max.	0.5 mA

Output delay with resistive load

• "0" to "1", max.	100 μ s
• "1" to "0", max.	500 μ s

Parallel switching of two outputs	
• for logic links	Yes
• for uprating	No
• for redundant control of a load	Yes
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz; According to IEC 60947-5-1, DC-13
• on lamp load, max.	10 Hz
Total current of the outputs	
• Current per channel, max.	0.5 A; see additional description in the manual
• Current per group, max.	4 A; see additional description in the manual
• Current per module, max.	8 A; see additional description in the manual
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Isochronous mode	
Execution and activation time (TCO), min.	70 µs
Bus cycle time (TDP), min.	250 µs
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	
• Diagnostic alarm	Yes
• Maintenance interrupt	Yes
Diagnoses	
• Monitoring the supply voltage	Yes
• Wire-break	Yes
• Short-circuit	Yes
• Group error	Yes
Diagnostics indication LED	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• MAINT LED	Yes; Yellow LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green LED
• Channel status display	Yes; green LED
• for channel diagnostics	Yes; red LED
• for module diagnostics	Yes; red LED
Potential separation	
Potential separation channels	
• between the channels	No
• between the channels, in groups of	8

- between the channels and backplane bus

Yes

Isolation

Isolation tested with 707 V DC (type test)

Standards, approvals, certificates

Suitable for safety functions No

Suitable for safety-related tripping of standard modules Yes; From FS02

Highest safety class achievable for safety-related tripping of standard modules

- Performance level according to ISO 13849-1 PL d
- Category according to ISO 13849-1 Cat. 3
- SILCL according to IEC 62061 SILCL 2

Ambient conditions

Ambient temperature during operation

- horizontal installation, min. -30 °C; From FS03
- horizontal installation, max. 60 °C
- vertical installation, min. -30 °C; From FS03
- vertical installation, max. 40 °C

Altitude during operation relating to sea level

- Installation altitude above sea level, max. 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual

Dimensions

Width 35 mm

Height 147 mm

Depth 129 mm

Weights

Weight, approx. 230 g

last modified: 09/03/2020