



expansion module switched Ethernet PROFINET, plug-in, for 7KM PAC3200 / 4200 / 3VA COM100 / 800

Model		
product brand name	SETRON	
product designation	Switched Ethernet PROFINET expansion module	
General technical data		
MTBF	215.6 y	
galvanic isolation	Maximum insulation voltage: 500V AC	
reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	P	
degree of pollution	2 according to IEC 61131	
Protection class		
protection class IP	IP20	
combustibility class acc. to UL 94	V 0	
suitability for use	No	
• reactive power meter		
Connections		
type of electrical connection	2 x RJ45 socket	
Mechanical Design		
height	63 mm	
width	43 mm	
depth	22 mm	
fastening method	pluggable	
Environmental conditions		
ambient temperature / during operation		
• minimum	-5 °C	
• maximum	55 °C	
ambient temperature / during storage		
• minimum	-25 °C	
• maximum	70 °C	
Certificates		
reference code / acc. to DIN EN 61346-2	P	
General Product Approval		
EMC	Declaration of Conformity	other

[Miscellaneous](#)

[KC](#)



[Manufacturer Declaration](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=7KM9300-0AE01-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7KM9300-0AE01-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=7KM9300-0AE01-0AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

