

AZM201Z-ST-T-AS-P



- Long life
- Double-insulated
- 40 mm x 244 mm x 50 mm
- Thermoplastic enclosure
- High holding force 2000
- Integrated AS-Interface
- I-variants with coding level HIGH to ISO 14119
- Interlock with protection against incorrect locking.
- Solenoid interlock with integrated AS-i Safety Interface
- Universal repeatedly teachable or individual coding because of the RFID technology

Data

Ordering data

Product type description	AZM201Z-ST-T-AS-P
Article number (order number)	103025866
EAN (European Article Number)	4030661524252
eCl@ss number, Version 9.0	27-27-26-03
eCl@ss number, Version 11.0	27-27-26-03

Approval - Standards

Certificates	TÜV
	cULus
	ASi-SaW
	EAC
	FCC
	IC

General data

Product name	Z 256 roller lever 7H-2138
--------------	----------------------------

Standards	ISO 13849-1 IEC 61508 IEC 60947-5-3 ISO 14119 IEC 62061 EN 62026-2
general information	Universal coding
Coding level according to ISO 14119	Low
Active principle	RFID
Enclosure material	Glass-fibre, reinforced thermoplastic
Gross weight	537.8 g
Time to readiness, maximum	4,000 ms
Reaction time, maximum	100 ms
Duration of risk, maximum	200 ms

General data - Features

Power to unlock	Yes
Guard locking monitored	Yes
Latching	Yes
Manual release	Yes
Safety functions	Yes
Integral System Diagnostics, status	Yes
Number of actuating directions	2

Safety appraisal

Standards	ISO 13849-1 IEC 62061 IEC 61508
-----------	---------------------------------------

Safety appraisal - Interlocking

Performance level, up to	e
Control category	4
PFH-value	1.81×10^{-9} /h
PFD value	1.59×10^{-4}
Safety Integrity Level (SIL), suitable for applications in	3
Mission Time	20 Year(s)

Mechanical data

Mechanical life, minimum	1,000,000 Operations
Clamping force in accordance with ISO14119 F_{zh}	2,000 N
Clamping force, maximum F_{max}	2,600 N
Latching force	30 N

Actuating speed, maximum	0.2 m/s
Tightening torque for the fixing screws, maximum	8 Nm

Mechanical data - Connection technique

Terminal Connector	Connector plug M12, 4-pole, (A-coding)
--------------------	--

Mechanical data - Dimensions

Length of sensor	50 mm
Width of sensor	40 mm
Height of sensor	220 mm

Ambient conditions

Degree of protection	IP66 to IEC 60529 IP67 to IEC 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+60 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+85 °C
Relative humidity, minimum	10 %
Relative humidity, maximum	95 %
Note (Relative humidity)	non-condensing non-icing
Resistance to vibrations to EN 60068-2-6	10 ... 150 Hz, amplitude 0.35 mm
Resistance to shock	30 g / 11 ms
Protection rating	III

Ambient conditions - Insulation value

Rated impulse withstand voltage U_{imp}	0.8 kV
Overvoltage category	III
Degree of pollution to IEC/EN 60664-1	3

Electrical data

Switching frequency, maximum	1 Hz
------------------------------	------

Electrical data - AS Interface

AS-i Operating voltage, minimum	26.5 VDC
AS-i Operating voltage AS-i maximum	31.6 VDC
Note (AS-i Operating voltage)	Protection against polarity reversal
AS-i Current consumption, maximum	100 mA

Electrical data - AS-Interface specification

AS-i Specification	Safety-Slave
AS-i Version	V 3.0
AS-i Profile	S-7.B.F.E
AS-i, IO-Code	0x7
AS-i, ID-Code	0xB
AS-i, ID-Code1	0xF
AS-i, ID-Code2	0xE
AS-i Input, Channel 1	Data bits DI 0 / DI 1 = dynamic code transmission
AS-i Input, Channel 2	Data bits DI 2 / DI 3 = dynamic code transmission
AS-i Outputs, DO 0	Solenoid control
AS-i Outputs, DO 1	No Function
AS-i Outputs, DO 2	No Function
AS-i Outputs, DO 3	No Function
AS-i Parameter bits, P0	Safety guard and actuator detected
AS-i Parameter bits, P1	Solenoid interlock locked
AS-i Parameter bits, P2	Magnet voltage in tolerance range
AS-i Parameter bits, P3	Internal device error (FID)
Note (AS-i Parameter bits)	FID: periphery error
AS-i Input module address	0
Note (AS-i Input module address)	Preset to address 0, can be changed through AS-interface bus master or hand-held programming device

Electrical data - Auxiliary voltage

Rated operating voltage	24 VDC -15% / +10% (stabilised PELV)
Operating current	500 mA

Status indication

Note (LED switching conditions display)	Status and diagnostics: Transmitter + receiver (2) LED red: Internal device error (3) LED yellow: Device condition
---	--

Pin assignment

PIN 1	AS-Interface +
PIN 2	Aux - (P)
PIN 3	AS-Interface -
PIN 4	Aux + (P)

Scope of delivery

Included in delivery	Actuators must be ordered separately.
----------------------	---------------------------------------

Accessory

Recommendation (actuator) AZ/AZM201-B1
AZ/AZM201-B30

Ordering code

Product type description:
AZM201(1)(2)-ST-T-AS(3)
P

(1)

Z Solenoid interlock monitored

NB, MBN, BN Actuator monitored

BZ Combined monitoring of actuator and solenoid interlock

(2)

without Standard coding

I1 Individual coding

I2 Individual coding, re-teaching enabled

(3)

without Power to unlock

A Power to lock

P

P Magnet supply 24 VDC (AUX)

Pictures

Product picture (catalogue individual photo)



ID: kazm2f51


| 441,1 kB | .jpg | 134.761 x 625.122 mm - 382 x 1772

Pixel - 72 dpi

| 218,5 kB | .png | 74.083 x 343.606 mm - 210 x 974

Pixel - 72 dpi

Dimensional drawing basic component



ID: 5azm2m75

| 7,2 kB | .png | 74.083 x 91.369 mm - 210 x 259 Pixel
- 72 dpi

| 253,1 kB | .jpg | 352.778 x 434.975 mm - 1000 x
1233 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 04/05/2021 10:25:05