

Price* : 1518.00 USD



Main

Range of product	Modicon TSX Micro automation platform
Product or component type	Relay discrete output module
Discrete output number	32 screw terminal block
Contacts type and composition	NO

Complementary

Output voltage limits	19...264 V AC 10...34 V DC
[Ith] conventional free air thermal current	2 A
Power consumption in VA	50 VA 24 V AC-12 resistive 24 VA 24 V AC-15 inductive 100 VA 48 V AC-12 resistive 200 VA 110...120 V AC-12 resistive 200 VA 200...240 V AC-12 resistive 50 VA 48 V AC-15 inductive 50 VA 110...120 V AC-15 inductive 50 VA 200...240 V AC-15 inductive
Power consumption in W	24 V DC-12 resistive 24 V DC-13 inductive
Response time	< 10 ms
Current consumption	175 mA
Power dissipation in W	3.5 W
Isolation voltage	1500 V 1 s
Insulation resistance	>= 10 mOhm

Ordering and shipping details

Category	22556 - TSX MICRO, PL7 MICRO & ACCESS
Discount Schedule	PC14
GTIN	00785901761570

Nbr. of units in pkg.	1
Package weight(Lbs)	2.21
Returnability	N
Country of origin	FR

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0919 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity

Contractual warranty

Warranty period	18 months
-----------------	-----------

Pre-Actuators/Outputs Connections

Wiring Diagram

