

Product availability: Non-Stock - Not normally stocked in distribution facility



Commercial status

This Product is Obsolete :

 This Product is Obsolete

Main

Range of product	Modicon Premium Automation platform
Product or component type	ISP Plus weighing module

Complementary

Kit composition	TSXISPY101 module TSXXBTN410 weight indicator Magelis
Number of measurement input	1
Resolution	1048576 points
Analogue input resolution	20 bits
Measuring rate	50 measurements per second
Input impedance	> 1 MOhm
Input compatibility	Load cell 1...8 350 Ohm yes <984.25 ft (300 m)
Sensor power supply	10 V DC
Output compatibility	Discrete reflex 2 positive
Discrete output voltage	24 V DC
Discrete output current	500 mA
Response time on output	1 ms
Transmission rate	9.6 kbit/s RS485 non isolated <= 30 m discrete reflex weight indicator
Voltage division	1 MV
Maximum cable distance between devices	9.84 Ft (3 m) for module/weight indicator
Electrical connection	1 connector screw terminal block for connecting 2 discrete reflex 1 female connector SUB-D 15 for the indicator input 1 female connector SUB-D 9 for RS485 serial link to the weight indicator
Marking	CE
Current consumption	145 mA 24 V rack 150 mA 5 V DC
Module format	Standard
Net Weight	2.25 Lb(US) (1.02 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Ambient air temperature for operation	32...140 °F (0...60 °C)
Ambient air temperature for storage	-13...158 °F (-25...70 °C)
Relative humidity	10...95 % without condensation for operation 5...95 % without condensation for storage
Operating altitude	0...6561.68 ft (0...2000 m)
Product certifications	SDM No 97.06

Ordering and shipping details

Category	22558 - TSX PREMIUM, ATRIUM & PL7 PRO
Discount Schedule	PC22
GTIN	00785901522768
Nbr. of units in pkg.	1
Package weight(Lbs)	4.41 Lb(US) (2.00 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	9.84 In (25 cm)
Package 1 width	10.24 In (26 cm)
Package 1 Length	11.02 In (28 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
---------------------------	--

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Post commercialisation**