

# Product data sheet

## Characteristics

# TSXP572634MC

Unity processor - Transparent Ready - 8 racks (12 slots), 16 racks (4/6/8 slots)

Product availability : Non-Stock - Not normally stocked in distribution facility

Price\* : 5,157.75 USD



## Commercial status

Discontinued on: 02 December 2020

To be end-of-service on: 31 December 2025

⚠ Restricted Sales for Services

## Main

Range of product	Modicon Premium Automation platform
Product or component type	Unity processor
Software designation	Unity Pro

## Complementary

Concept	Transparent Ready
Number of racks	16 4/6/8 slots 8 12 slots
Number of slots	64 96 128
Discrete I/O processor capacity	1024 I/O
Analogue I/O processor capacity	80 I/O
Number of application specific channel	24
Number of process control channel	10 up to 30 simple loops
Integrated connection type	Ethernet TCP/IP RJ45
Port Ethernet	10BASE-T/100BASE-TX
Communication module processor capacity	4 1
Memory description	Internal RAM (with PCMCIA card) 160 kB data Internal RAM (with PCMCIA card) 768 kB program Internal RAM (without PCMCIA card) 160 kB program and data PCMCIA card 16384 kB additional data storage
Maximum size of object areas	64 %KWi constant words located internal data 64 %MWi internal words located internal data 64 kB (DFB and EFB function blocks) unlocated internal data 64 kB (elementary and derived data) unlocated internal data 8132 %Mi located internal bits
Application structure	1 fast task 1 master task 64 event tasks
Execution time per instruction	0.19 µs Boolean without PCMCIA card 0.25 µs word or fixed-point arithmetic without PCMCIA card 1.75...2.6 µs floating points with PCMCIA card

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

	1.75...2.6 $\mu$ s floating points without PCMCIA card 0.21 $\mu$ s Boolean with PCMCIA card 0.42 $\mu$ s word or fixed-point arithmetic with PCMCIA card
Number of instructions per ms	2.53 Kinst/ms 65 % Boolean + 35 % fixed arithmetic with PCMCIA card 3.7 Kinst/ms 100 % Boolean with PCMCIA card 3.71 Kinst/ms 65 % Boolean + 35 % fixed arithmetic without PCMCIA card 4.76 Kinst/ms 100 % Boolean without PCMCIA card
System overhead	0.3 ms fast task 1 ms master task
Marking	CE
Local signalling	for Ethernet TCP/IP port ready (RUN) 1 LED (green) for processor running (RUN) 1 LED (green) for collision detection (COL) 1 LED (red) for Ethernet TCP/IP port fault (ERR) 1 LED (red) for I/O module or configuration fault (I/O) 1 LED (red) for processor or system fault (ERR) 1 LED (red) for activity on TER or AUX terminal port (TER) 1 LED (yellow) for Ethernet link diagnostics (STS) 1 LED (yellow) for reception activity (RX) 1 LED (yellow) for transmission activity (TX) 1 LED (yellow)
Current consumption	1650 mA 5 V DC
Module format	Double
Net Weight	0.09 lb(US) (0.042 kg)

## Environment

Standards	73/23/EEC CSA C22.2 No 213 Class I Division 2 Group C CSA C22.2 No 142 89/336/EEC 92/31/EEC CSA C22.2 No 213 Class I Division 2 Group B IEC 61131-2 CSA C22.2 No 213 Class I Division 2 Group D 93/68/EEC CSA C22.2 No 213 Class I Division 2 Group A UL 508
Product certifications	DNV GL RMRS ABS BV LR RINA
Ambient air temperature for operation	32...140 °F (0...60 °C)
Ambient air temperature for storage	-13...158 °F (-25...70 °C)
Relative humidity	10...95 % without condensation for operation 5...95 % without condensation for storage
Operating altitude	0...6561.68 ft (0...2000 m)
Protective treatment	TC Conformal coating Humiseal 1A33
IP degree of protection	IP20
Pollution degree	2

## Ordering and shipping details

Category	22558 - TSX PREMIUM, ATRIUM & PL7 PRO
Discount Schedule	PC22
GTIN	03595863942279
Nbr. of units in pkg.	1
Package weight(Lbs)	2.2 lb(US) (1.00 kg)
Returnability	No
Country of origin	FR

## Packing Units

Package 1 Height	3.74 in (95.000 mm)
Package 1 width	7.09 in (180.000 mm)
Package 1 Length	10.24 in (260.000 mm)

## Contractual warranty

Warranty	18 months
----------	-----------

## TSXP572634MC is replaced by:



### Harsh environment BMEP582020H

processor module M580 - Level 2 - Distributed Harsh

Qty 1

Reason for Substitution: End of life | Substitution date: 31 December 2017