




Multifunction display for monitoring analogue standard signals

DISPLAY/AX460/PNP OUT/AC/DC




Product characteristics		
Dimensions	[mm]	48 x 112 x 116
Application		
Application	displaying and monitoring analogue signals; e.g. pressure sensors, temperature sensors or flow sensors	
Electrical data		
Frequency AC	[Hz]	50...60
Operating voltage	[V]	115...230 AC / 18...30 DC
Current consumption	[mA]	100
Inputs / outputs		
Number of inputs and outputs	Number of analogue inputs: 2; Number of digital outputs: 4	
Inputs		
Number of analogue inputs	2	
Outputs		
Number of digital outputs	4	
Overload protection	yes	
Operating conditions		
Ambient temperature	[°C]	-20...60
Storage temperature	[°C]	-25...70
Protection	IP 65	
Protection rating terminals	IP 20	
Tests / approvals		
EMC	EN 61000-6-2	
	EN 61000-6-3	
	EN 61000-6-4	



Multifunction display for monitoring analogue standard signals

DISPLAY/AX460/PNP OUT/AC/DC

Mechanical data		
Weight	[g]	350.5
Type of mounting		panel cutout: 91 x 43 mm
Dimensions	[mm]	48 x 112 x 116
Materials		Noryl UL94-V-0
Displays / operating elements		
Display	colour display	full graphic LCD display, touch screen
Electrical connection		
screw terminals:		
Connection		



NC not used