


# EBC001



## Splitter box

ZDO4H050MSS0000-00STAK120MSS



Application	
Special feature	Free from silicone; Gold-plated contacts
Free from silicone	yes
Electrical data	
Operating voltage [V]	< 30 AC/DC; ("supply class 2" to cULus)
Max. current load per module/slot [A]	4
Max. current load total [A]	12

# EBC001



## Splitter box

ZDO4H050MSS0000-00STAK120MSS

Operating conditions		
Ambient temperature	[°C]	-25...80
Protection		IP 67
Tests / approvals		
UL approval	Enclosure type	Type 1
Mechanical data		
Weight	[g]	236.5
Dimensions	[mm]	33 x 60 x 118.2
Materials		PA
Moulded-body material		PA / PA
Number of ports splitter box		4
Connector type		M12
Accessories		
Items supplied		Protective caps: 2 labels: 4
Remarks		
Pack quantity		1 pcs.
Electrical connection - Connection		
Connector: 1 x M23; Moulded body: PA; Contacts: gold-plated; Tightening torque: 0.8...1.5 Nm		


# EBC001



## Splitter box

ZDO4H050MSS0000-00STAK120MSS

### Connection



### Electrical connection - slot

Connector: 4 x M12; Moulded body: PA; Contacts: gold-plated; Tightening torque: 0.8...1.5 Nm

